




Higgs-4 is a highly integrated single chip EPC global Class 1 Gen 2 UHF RFID Tag IC that further enhances Higgs-family performance while being optimized for the highest volume applications to aid the mass-market adoption of RFID technology.



Applications

- Retail Item Level Tagging
- Supply Chain Management
- Vehicle Tracking
- Product Authentication
- Asset Inventory and Tracking
- Baggage Handling and Tracking

FEATURE	DESCRIPTION	BENEFIT
Further Increases Alien's Industry Leading Read Sensitivity	Industry leading tag performance especially in challenging RF environments.	Saves money: Reduces the number of read points and/or minimizes tag size.
Read Sensitivity	Up to -19 dBm*	Increased write performance, writing multiple words in a single command and writing to multiple-tags simultaneously, massively decreases the cost and time associated with programming millions of tags. Proven at 3,600 tags/minute (measured performance).
Write Sensitivity	Up to -16 dBm*	
<i>QuickWrite</i> ™	The ability to write a complete bank of memory with one command.	
<i>BlastWrite</i> ™	An IC mass-encoding capability. Takes a single write-cycle to encode multiple tags.	

*on a 2.15 dBi gain dipole antenna

Features:

- › Designed to meet EPCglobal Gen2 (V 1.2.0) and ISO/IEC 18000-6C
- › Worldwide operation in the RFID UHF bands (840-960 MHz)
- › 448-Bits of NVM/RAM Memory
 - Up to 128-EPC Bits (nominally 96 bits)
 - 128 User Bits
 - 64 Bit Unique TID
 - 32 Bit Access and 32 bit Kill Passwords
- › Pre-Programmed with a unique, unalterable 64-bit serial number
- › User Memory can be Block Perma-Locked as well as read password protected in 32 Bit Blocks
- › Low power operation for both read and program
- › QuickWrite™ / BlastWrite™- High speed chip & mass programming
- › Dynamic Authentication™ - anti-cloning/anti-counterfeit technology
- › Exceptional operating range, up to 11m with appropriate antenna.

Product Overview:

Higgs-4 operates at extremely low power levels yet still provides sufficient backscatter signal to read tags at extended range. It can also be programmed at low RF power and at high speed using Alien's *QuickWrite*™ single instruction bank-write capability. *BlastWrite*™ can also be used to program multiple tags simultaneously for mass-encoding in high-volume retail applications. Higgs-4 also fully supports the latest industry standard serialization schemes.

Higgs-4 offers a mass-market optimized but flexible memory architecture that provides for the optimum allocation of EPC and User memory for different use cases such as legacy part numbering systems and service history. User memory can also be read and or write locked on 32-bit boundaries, supporting a variety of public/private usage models.

Higgs-4 contains a number of unique advanced features. Dynamic Authentication™ provides a unique non-reproducible fingerprint that can be used for anti-cloning and anti-counterfeiting.

The IC also features factory programmed 64-bit serial number that cannot be altered. In conjunction with the EPC code, this provides a unique identification for the tagged item.

**Operating Conditions & Electrical Characteristics**

Symbol	Parameter	Conditions / Capability	Min	Typ	Max	Units
Operating Conditions						
T_A	Operating Temperature		-50		+85	°C
f_{in}	Operating Frequency		840		960	MHz
Electrical Characteristics						
S_R	Sensitivity during Read	Bare die measurement, 50 Ohm impedance, Calibrated Voyantic™ measurement system		-16.8		dBm
S_W	Sensitivity during Write			-13.8		dBm
I_S	Interference Signal Suppression			-4		dB
R_p	Equivalent input parallel resistance	At -20.5 dBm input power		1800		Ohms
C_p	Equivalent input parallel Capacitance	At -20.5 dBm input power		0.95		pF
D_{ret}	Data Retention			50		Years
P_{cycl}	Programming Cycles at 25°C			100,000		Cycles

Memory Map

Bank	Address	Description	Memory	Bits
User	00h – 7Fh	User	NVM	128
TID	60h – BFh	Device Configuration	ROM-NVM	96
	20h – 5Fh	Unique Tag ID Unalterable	NVM	64
	00h – 1Fh	TID EPC/TMD/TMDID/TMN	ROM	32
EPC	20h – 9Fh	EPC #	NVM	128
	10h – 1Fh	EPC-PC	NVM	16
	00h – 0Fh	EPC-CRC	RAM	16
Reserved	20h – 3Fh	RES-Access Pwd, EPC optional	NVM	32
	00h – 1Fh	RES-Kill Pwd	NVM	32


Ordering Information

Part	Model Number	Description
Higgs™ 4 IC	ALC-370-IC	Bumped, Tested, Ground & Sawn IC's. Provided on 8 Inch Wafer, UV Tape Mounted (SEMI/JIS Standard Metal Film Frame)
	ALC-370-SOT	SMD Package: SOT-323





Wafer and Die Orientation



February 21, 2020

Copyright© 2020 Alien Technology LLC. All rights reserved.

Alien, Alien Technology, the Alien Technology logo, Spider, Higgs, Dynamic Authentication, QuickWrite, BlockWrite, Squiggle, and the Squiggle logo are trademarks or registered trademarks of Alien Technology Corporation in the U.S. and other countries.

HANDLING PRECAUTIONS Observe standard handling practices to minimize ESD.

DISCLAIMER Application recommendations are guidelines only - actual results may vary and should be confirmed. This is a general purpose product not designed or intended for any specific application.

This product is covered by one or more of the following U.S. patents: 7967204, 7931063, 7868766, 7737825, 7716208, 7716160, 7688206, 7671720, 7659822, 7619531, 7615479, 7598867, 7580378, 7576656, 7562083, 7561221, 7559486, 7559131, 7554451, 7551141, 7542301, 7542008, 7522055, 7500610, 7489248, 7453705, 7452748, 7425467, 7417306, 7411503, 7385284, 7377445, 7364084, 7353598, 7342490, 7324061, 7321159, 7301458, 7295114, 7288432, 7265675, 7262686, 7193504, 7173528, 7172910, 7172789, 7141176, 7113250, 7101502, 7080444, 7070851, 7068224, 7046328, 6998644, 6988667, 6985361, 6980184, 6970219, 6952157, 6942155, 6933848. Other patents pending.

This product is licensed under patents of Round Rock Research, LLC, for use solely with UHF RFID Readers (such as Alien reader products) that are licensed under an agreement with Round Rock Research, LLC.



Alien Technology
845 Embedded Way
San Jose, CA 95138
866-RFID NOW
www.alientechnology.com